



LED Display

Product Data Sheet

LTD-6402JD-02

Spec No.: DS30-2001-199

Effective Date: 11/27/2001

Revision: -

LITE-ON DCC

RELEASE

FEATURES

- * 0.56 inch (14.22 mm) DIGIT HEIGHT.
- * CONTINUOUS UNIFORM SEGMENTS.
- * LOW POWER REQUIREMENT.
- * EXCELLENT CHARACTERS APPEARANCE.
- * HIGH BRIGHTNESS & HIGH CONTRAST.
- * WIDE VIEWING ANGLE.
- * SOLID STATE RELIABILITY.
- * CATEGORIZED FOR LUMINOUS INTENSITY.


DESCRIPTION

The LTD-6402JD-02 is a 0.56 inch (14.22 mm) height digit display. The device utilizes AlInGaP hyper red LED chips which are made from AlInGaP on a non-transparent GaAs substrate, and have light gray face and white segment color.

DEVICE


PART NO.	DESCRIPTION
AlInGaP HYPER RED	Common Anode Rt. Hand Decimal
LTD-6402JD-02	

PACKAGE DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm (0.01“) unless otherwise noted.

INTERNAL CIRCUIT DIAGRAM



PIN CONNECTION

No.	CONNECTION
1	CATHODE E (DIGIT 1, DIGIT 2)
2	CATHODE D (DIGIT 1, DIGIT 2)
3	CATHODE D.P. (DIGIT 1, DIGIT 2)
4	CATHODE C (DIGIT 1, DIGIT 2)
5	CATHODE G (DIGIT 1, DIGIT 2)
6	NO CONNECTION
7	CATHODE B (DIGIT 1, DIGIT 2)
8	NO CONNECTION
9	COMMON ANODE (DIGIT 2)
10	CATHODE F (DIGIT 1, DIGIT 2)
11	CATHODE A (DIGIT 1, DIGIT 2)
12	COMMON ANODE (DIGIT 1)

ABSOLUTE MAXIMUM RATING AT Ta=25°C

PARAMETER	MAXIMUM RATING	UNIT
Power Dissipation Per Segment	70	mW
Peak Forward Current Per Segment (1/10 Duty Cycle, 0.1ms Pulse Width)	90	mA
Continuous Forward Current Per Segment	25	mA
Derating Linear From 25°C Per Segment	0.28	mA/°C
Reverse Voltage Per Segment	5	V
Operating Temperature Range	-35°C to +105°C	
Storage Temperature Range	-35°C to +105°C	
Solder Temperature: max 260°C for max 3sec at 1.6mm[1/16inch] below seating plane.		







ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta=25°C

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I _v	320	700		μcd	I _F =1mA
Peak Emission Wavelength	λ _p		650		nm	I _F =20mA
Spectral Line Half-Width	Δλ		20		nm	I _F =20mA
Dominant Wavelength	λ _d		639		nm	I _F =20mA
Forward Voltage Per Segment	V _F		2.1	2.6	V	I _F =20mA
Reverse Current Per Segment	I _R			100	μA	V _R =5V
Luminous Intensity Matching Ratio	I _v -m			2:1		I _F =10mA

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)



NOTE : JD=AlInGaP HYPER RED