



SMD LED
Product Data Sheet
LTSA-G6SVUAETU

Spec No.:
Created Date: 2017/10/31
Revision: 1.0

SMD LED
LTSA-G6SVUAETU

SMD LED

LTSA-G6SVUAETU

<u>Rev</u>	<u>Description</u>	<u>By</u>	<u>Date</u>
1	New datasheet	Ryan Chen	10/31/2017
Above data for PD and Customer tracking only			

Customer Name:

Customer Signature:

LiteON Sales Signature:

Print Name:

Print Name:

SMD LED LTSA-G6SVUAETU

1. Description

SMD LEDs from Lite-On are available in miniature sizes and special configurations for automated PC board assembly and space-sensitive applications. These SMD LEDs are suitable for use in a wide variety of Automotive.


1.1 Features

- Meet ROHS
- Package in 12mm tape on 7" diameter reels
- Preconditioning: accelerate to JEDEC level 2
- Qualification is refer to AEC-Q101D Ver.D
- EIA STD package
- I.C. compatible
- Compatible with automatic placement equipment
- Compatible with infrared reflow solder process

1.2 Applications

- Automotive: accessory applications

2. Package Dimensions



Part No.	Lens Color	Source Color
LTSA-G6SVUAETU	Orange	InGaN Yellow

Notes:

1. All dimensions are in millimeters.
2. Tolerance is ± 0.2 mm (.008") unless otherwise noted.
3. CATHODE lead frame is heat sink of LED.

3. Rating and Characteristics

3.1 Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

Parameter	LTSA-G6SVUAETU	Unit
Power Dissipation	900	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	500	mA
DC Forward Current	250	mA
Reverse Voltage	Not designed for reverse operation	
Operating Temperature Range	-40°C to +110°C	
Storage Temperature Range	-40°C to +110°C	

3.2 Thermal Characteristics

Parameter	Symbol	TYP.	MAX.	Unit
Thermal Resistance (Junction – Ambient) ^{Note}	$R_{th JA}$	45	-	$^\circ\text{C}/\text{W}$
Thermal Resistance (Junction – Solder Point) ^{Note}	$R_{th JS}$	25	-	$^\circ\text{C}/\text{W}$
Junction Temperature	T_J	-	150	$^\circ\text{C}$


Note: $R_{th JA}$ Measurement Condition

Substrate: FR4 ($t=1.6\text{mm}$) / Pattern Size: 16mm^2

SMD LED
 LTSA-G6SVUAETU

3.3 Suggest IR Reflow Condition for Pb Free Process:

IR-Reflow Soldering Profile for lead free soldering (Acc. to J-STD-020)



SMD LED LTSA-G6SVUAETU

3.4 Electrical / Optical Characteristics at $T_a=25^\circ C$

Parameter	Symbol	Part No. LTSA-	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	IV	G6SVUAETU	4.5	-	11.2	cd	IF = 140mA Note 1
Viewing Angle	$2\theta_{1/2}$	G6SVUAETU	-	120	-	deg	Note 2 (Fig.2)
Chromaticity Coordinates	Cx	G6SVUAETU		0.56			IF = 140mA Note 3
	Cy	G6SVUAETU		0.42			
Forward Voltage	VF	G6SVUAETU	2.8	-	3.6	V	IF = 140mA Note 4
Reverse Current	IR	G6SVUAETU	-		10	μA	VR = 5V Note 5

Notes:

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
3. The dominant wavelength, λ_d is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device. Tolerance on each Hue bin (x, y) bin is +/- 0.01.
4. Forward Voltage Tolerance is +/- 0.1 volt.
5. Reverse voltage (VR) condition is applied to IR test only. The device is not designed for reverse operation

4. Bin Rank

Batch Description on Label: Vf / Iv / Hue (Ex. 24/EA/A20)

4.1 VF Rank

Forward Voltage (Vf)		Unit : V @140mA	
Bin Code		Min.	Max.
24		2.8	3.0
64		3.0	3.2
A4		3.2	3.4
E4		3.4	3.6

Tolerance on each Voltage bin is +/-0.1V

4.2 IV Rank

Bin Code	Luminous Intensity (Iv) Unit : cd @140mA		Unit : lm @140mA	
	Min.	Max.	Min.	Max.
DA	4.5	5.6	13.1	16.0
DB	5.6	7.1	16.0	20.6
EA	7.1	9.0	20.6	26.1
EB	9.0	11.2	26.1	32.5

Tolerance on each Intensity bin is +/-11%

SMD LED LTSA-G6SVUAETU


4.3 Color Rank

Bin Code	Color Bin Limits				
	CIE-	Point1	Point2	Point3	Point4
A10	x	0.5775	0.5843	0.5622	0.5576
	y	0.4132	0.4151	0.4372	0.4326
A20	x	0.5705	0.5775	0.5576	0.5499
	y	0.4111	0.4132	0.4326	0.4249
B10	x	0.5775	0.5843	0.6062	0.6000
	y	0.4132	0.4151	0.3930	0.3930
B20	x	0.5705	0.5775	0.6000	0.5940
	y	0.4111	0.4132	0.3930	0.3930

Tolerance on each Hue bin (x, y) bin is +/- 0.01.

4.4 Chromaticity Coordinate

1931 CIE chromaticity



5. Typical Electrical / Optical Characteristics Curves.

25°C Ambient Temperature Unless Special Noted




Fig. 1 RELATIVE INTENSITY VS. WAVELENGTH




Fig. 2 SPATIAL DISTRIBUTION




Fig. 3 FORWARD VOLTAGE V.S.
FORWARD CURRENT




Fig. 4 RELATIVE LUMINOUS INTENSITY
V.S. FORWARD CURRENT




Fig. 5 FORWARD CURRENT
DERATING CURVE


6. User Guide

6.1 Cleaning


Do not use unspecified chemical liquid to clean LED they could harm the package. If cleaning is necessary, immerse the LED in ethyl alcohol or isopropyl alcohol at normal temperature for less than one minute.

6.2 Recommend Printed Circuit Board Attachment Pad

Infrared: Reflow Soldering




6.3 Package Dimensions of Tape And Reel



Note:

1. All dimensions are in millimeters (inches).

6.4 Package Dimensions of Reel



Notes:

1. Empty component pockets sealed with top cover tape.
2. 7 inch reel 1000 pieces per reel.
3. Minimum packing quantity is 500 pieces for remainders.
4. The maximum number of consecutive missing lamps is two.
5. In accordance with ANSI/EIA 481 specifications.

7. Cautions

7.1 Application

The LEDs described here are intended to be used for ordinary electronic equipment (such as office equipment, communication equipment and household applications). Consult Liteon's Sales in advance for information on applications in which exceptional reliability is required, particularly when the failure or malfunction of the LEDs may directly jeopardize life or health (such as in aviation, transportation, traffic control equipment, medical and life support systems and safety devices).

7.2 Storage

This product is qualified as Moisture sensitive Level 2 per JEDEC J-STD-020 Precaution when handling this moisture sensitive product is important to ensure the reliability of the product.

The package is sealed:

The LEDs should be stored at 30°C or less and 70%RH or less. And the LEDs are limited to use within one year, while the LEDs is packed in moisture-proof package with the desiccants inside.

The package is opened:

The storage ambient for the LEDs should not exceed 30°C temperature and 60% relative humidity.

It is recommended that LEDs out of their original packaging are IR-reflowed within one year.

For extended storage out of their original packaging, it is recommended that the LEDs be stored in a sealed container with appropriate desiccant, or in a desiccators with nitrogen ambient.

LEDs stored out of their original packaging for more than one year should be baked at about 60 °C for at least 48 hours before solder assembly.

7.3 Cleaning

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED if necessary.

7.4 Soldering

Recommended soldering conditions:

Reflow soldering		Soldering iron	
Pre-heat	150~200°C	Temperature	300°C Max.
Pre-heat time	120 sec. Max.	Soldering time	3 sec. Max.
Peak temperature	260°C Max.		(one time only)
Soldering time	10 sec. Max.(Max. two times)		

Notes:

Because different board designs use different number and types of devices, solder pastes, reflow ovens, and circuit boards, no single temperature profile works for all possible combinations.

However, you can successfully mount your packages to the PCB by following the proper guidelines and PCB-specific characterization.

LITE-ON Runs both component-level verification using in-house **KYRAMX98** reflow chambers and board-level assembly. The results of this testing are verified through post-reflow reliability testing. Profiles used at LITE-ON are based on JEDEC standards to ensure that all packages can be successfully and reliably surface mounted.

Figure on page3 shows a sample temperature profile compliant to JEDEC standards. You can use this example as a generic target to set up your reflow process. You should adhere to the JEDEC profile limits as well as specifications and recommendations from the solder paste manufacturer to avoid damaging the device and create a reliable solder joint.


SMD LED

LTSA-G6SVUAETU


7.5 Drive Method

A LED is a current-operated device. In order to ensure intensity uniformity on multiple LEDs connected in parallel in an application, it is recommended that a current limiting resistor be incorporated in the drive circuit, in series with each LED as shown in Circuit A below.

Circuit model A



Circuit model B



(A) Recommended circuit.

(B) The brightness of each LED might appear different due to the differences in the I-V characteristics of those LEDs.

7.6 ESD (Electrostatic Discharge)

Static Electricity or power surge will damage the LED.

Suggestions to prevent ESD damage:

- Use of a conductive wrist band or anti-electrostatic glove when handling these LEDs.
- All devices, equipment, and machinery must be properly grounded.
- Work tables, storage racks, etc. should be properly grounded.
- Use ion blower to neutralize the static charge which might have built up on surface of the LED's plastic lens as a result of friction between LEDs during storage and handling.

ESD-damaged LEDs will exhibit abnormal characteristics such as high reverse leakage current, low forward voltage, or "no lightup" at low currents.

To verify for ESD damage, check for "lightup" and V_f of the suspect LEDs at low currents.

The V_f of "good" LEDs should be $>2.0V@0.1mA$ for InGaN product and $>1.4V@0.1mA$ for AlInGaP product.

SMD LED
 LTSA-G6SVUAETU

8. Reliability Test

No.	Test item	Test condition	Sample Size Per Lot	Reference standard
2	Pre-conditioning	MSL 2 125°C, 24 hrs baking Moisture Soak 85°C/60% 168 hrs Interval: 15mins ~ 4 hours to do IR-Reflow	462	JESD22 A-113
5b+	High Temperature Forward Bias (HTFB)	Ta=70± 2°C IF: 250 mA 1000 hrs	77	JESD22 A-108
5b	High Temperature Forward Bias (HTFB)	Ta=110 ± 2°C IF: 100mA 1000 hrs	77	JESD22 A-108
7	Temperature Cycle (TC)	-40°C(+0, -10) to 110°C(+15,-0) 10min 10min 10min 1000 cycles	77	JESD22 A-104 Appendix 6
9a	High Temperature High Humidity Bias (HTHBB)	Ta=85 ± 2°C, 85 ± 5% RH IF: 200mA 1000 hrs	77	JESD22 A-101
10alt	Power and Temperature Cycle (PTC)	-40°C (+0, -10) to 85°C (+10,-0) 10 min 20 min 10 min IF: 200mA 1 cycle: 2 min. on / 2 min. off 15000 cycles (1000 hrs)	77	JESD22 A-105
11	ESD Characterization	HBM 2000V	30	JESD22-A114-FS
20	Resistance to Solder Heat	Tsld=260°C, 10sec. 3times	30	JESD22A-111
21	Solderability	Tsld = 245± 5°C, 5sec, Lead-free Solder	10	J-STD-002 JESD22B102

9. Others

The appearance and specifications of the product may be modified for improvement without prior notice.

10. Suggested Checking List

Training and Certification

1. Everyone working in a static-safe area is ESD-certified?
2. Training records kept and re-certification dates monitored?

Static-Safe Workstation & Work Areas

1. Static-safe workstation or work-areas have ESD signs?
2. All surfaces and objects at all static-safe workstation and within 1 ft measure less than 100V?
3. All ionizer activated, positioned towards the units?
4. Each work surface mats grounding is good?

Personnel Grounding

1. Every person (including visitors) handling ESD sensitive (ESDS) items wears wrist strap, heel strap or conductive shoes with conductive flooring?
2. If conductive footwear used, conductive flooring also present where operator stand or walk?
3. Garments, hairs or anything closer than 1 ft to ESD items measure less than 100V*?
4. Every wrist strap or heel strap/conductive shoes checked daily and result recorded for all DLs?
5. All wrist strap or heel strap checkers calibration up to date?

Note: *50V for InGaN LED.

Device Handling

1. Every ESDS items identified by EIA-471 labels on item or packaging?
2. All ESDS items completely inside properly closed static-shielding containers when not at static-safe workstation?
3. No static charge generators (e.g. plastics) inside shielding containers with ESDS items?
4. All flexible conductive and dissipative package materials inspected before reuse or recycles?

Others

1. Audit result reported to entity ESD control coordinator?
2. Corrective action from previous audits completed?
3. Are audit records complete and on file?