

EL Mini TOP VIEW LED 2214-C70301H-AM



Features

- Package : PLCC 2 package
- Color : Cool White
- Typ. Luminance Intensity : 2240 mcd @ 30mA
- Viewing angle : 120°
- ESD : 8KV
- MSL : 3
- Qualified AEC-Q102
- Corrosion Robustness Class A1
- The product itself will remain within RoHS compliant version.
- Compliance with EU REACH.
- Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm)

Application

- Automotive Interior lighting.

Contents

1. Characteristics	3
2. Absolute Maximum Ratings	4
3. Characteristics Graph.....	5
4. Binning Information	10
5. Part Number	13
6. Ordering Information	15
7. Mechanical Dimension.....	16
8. Recommended Soldering Pad.....	17
9. Reflow Soldering Profile.....	17
10. Packaging Information.....	18
11. Precaution for Use	20
12. Sulfur Test Criteria	21

1. Characteristics

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Current		I_F	6	30	60	mA	---
Luminous Intensity		I_v	1400	2240	4500	mcd	$I_F=30\text{mA}$
Forward Voltage		V_F	2.5	3.1	3.75	V	$I_F=30\text{mA}$
Viewing Angle		φ	---	120	---	deg	$I_F=30\text{mA}$
Color		CIE x	---	0.3	---	---	$I_F=30\text{mA}$
Color		CIE y	---	0.3	---	---	$I_F=30\text{mA}$
Thermal Resistance (Junction to Solder)	Real	$R_{th JS real}$	---	---	95	K/W	$I_F=30\text{mA}$
	Electrical	$R_{th JS el}$	---	---	75	K/W	$I_F=30\text{mA}$

Notes:

1. Luminous Flux measurement tolerance: $\pm 8\%$.
2. The data of Luminous Flux measured at thermal pad= 25°C .
3. Forward voltage measurement tolerance: $\pm 0.05\text{V}$.
4. Tolerance of Chromaticity Coordinates x,y : ± 0.005 .

2. Absolute Maximum Ratings


Parameter	Symbol	Ratings	Unit
Power Dissipation	P_d	210	mW
Forward Current	I_F	60	mA
Surge Current ($t \leq 10 \mu s$; $D = 0.005$; $T_s = 25 \text{ }^\circ\text{C}$)	I_{FM}	250	mA
Reverse Voltage	V_R	Not designed for reverse operation	V
Junction Temperature	T_J	125	$^\circ\text{C}$
Operating Temperature	T_{opr}	-40 ~ +110	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 ~ +110	$^\circ\text{C}$
ESD Sensitivity ($R = 1.5 \text{ k}\Omega$, $C = 100 \text{ pF}$)	ESD_{HBM}	8	kV
Soldering Temperature	Reflow	260 $^\circ\text{C}$ for 30sec	$^\circ\text{C}$

3. Characteristics Graph

Wavelength Characteristics Relative Spectral Distribution


@ Ts = 25°C, If=30mA

$$\Phi_V / \Phi_V (Max.) = f(\lambda)$$



Typical Diagram Characteristics of Radiation

$$\Phi_V / \Phi_V (0^\circ) = f(\varphi)$$




Notes:

1. φ is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
2. View angle tolerance is $\pm 5^\circ$.

Forward Current vs. Forward Voltage

@ Ts = 25°C


$$I_F = f(V_F)$$



Relative Luminous Intensity vs. Forward Current


@ Ts = 25°C

$$\Phi_V / \Phi_V(30mA) = f(I_F)$$




Chromaticity Coordinates Shift vs. Forward Current @ Ts = 25°C

$$\Delta CIE\ x, \Delta CIE\ y = f(I_F)$$




Relative Forward Voltage vs. Junction Temperature @ If=30mA

$$\Delta V_F = V_F - V_F(25^\circ C) = f(T_j)$$




Relative Luminous Intensity vs. Junction Temperature @ I_F=30mA

$$\Phi_v / \Phi_v(25^\circ C) = f(T_j)$$




Chromaticity Coordinates Shift vs. Junction Temperature @ I_F=30mA

$$\Delta CIE\ x, \Delta CIE\ y = f(T_j)$$




Forward Current Derating Curve

$$I_F = f(T_S)$$



Permissible Pulse Handling Capability

D=Duty cycle , $T_s = 25^\circ\text{C}$



4. Binning Information


Luminous Intensity Bins

Group Bin	Minimum Luminous Intensity (mcd)	Maximum Luminous Intensity (mcd)
L1	11.2	14
L2	14	18
M1	18	22.4
M2	22.4	28
N1	28	35.5
N2	35.5	45
P1	45	56
P2	56	71
Q1	71	90
Q2	90	112
R1	112	140
R2	140	180
S1	180	224
S2	224	280
T1	280	355
T2	355	450
U1	450	560
U2	560	710
V1	710	900
V2	900	1120
AA	1120	1400
AB	1400	1800
BA	1800	2240
BB	2240	2800
CA	2800	3550
CB	3550	4500
DA	4500	5600
DB	5600	7100
EA	7100	9000
EB	9000	11200
FA	11200	14000
FB	14000	18000
GA	18000	22400

Notes:

1. Luminous flux measurement tolerance: $\pm 8\%$.
2. Highlighted Black Box is possible output bins.

Standard Cool White Color Bin Structure



Cool White Color Bin Coordinates

Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y
L10	0.3582	0.3874	L20	0.3582	0.3715	L30	0.3582	0.3542
	0.3582	0.3978		0.3582	0.3874		0.3582	0.3715
	0.3680	0.4120		0.3680	0.4023		0.3680	0.3859
	0.3680	0.4023		0.3680	0.3859		0.3680	0.3695
K10	0.3484	0.3730	K20	0.3484	0.3571	K30	0.3484	0.3388
	0.3484	0.3841		0.3484	0.3730		0.3484	0.3571
	0.3582	0.3978		0.3582	0.3874		0.3582	0.3715
	0.3582	0.3874		0.3582	0.3715		0.3582	0.3542
J10	0.3386	0.3591	J20	0.3386	0.3426	J30	0.3386	0.3235
	0.3386	0.3709		0.3386	0.3591		0.3386	0.3426
	0.3484	0.3841		0.3484	0.3730		0.3484	0.3571
	0.3484	0.3730		0.3484	0.3571		0.3484	0.3388
I10	0.3288	0.3452	I20	0.3288	0.3282	I30	0.3288	0.3081
	0.3288	0.3577		0.3288	0.3452		0.3288	0.3282
	0.3386	0.3709		0.3386	0.3591		0.3386	0.3426
	0.3386	0.3591		0.3386	0.3426		0.3386	0.3235

Cool White Color Bin Coordinates

Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y	Bin Code	CIE_x	CIE_y
H10	0.3189	0.3302	H20	0.3197	0.3131	H30	0.3205	0.2956
	0.3183	0.3434		0.3189	0.3302		0.3197	0.3131
	0.3288	0.3577		0.3288	0.3452		0.3288	0.3282
	0.3288	0.3452		0.3288	0.3282		0.3288	0.3081
G10	0.3070	0.3120	G20	0.3100	0.2970	G30	0.3130	0.2840
	0.3045	0.3245		0.3070	0.3120		0.3100	0.2970
	0.3183	0.3434		0.3189	0.3302		0.3197	0.3131
	0.3189	0.3302		0.3197	0.3131		0.3205	0.2956
F10	0.2960	0.2955	F20	0.3005	0.2825	F30	0.3045	0.2715
	0.2919	0.3073		0.2960	0.2955		0.3005	0.2825
	0.3045	0.3245		0.3070	0.3120		0.3100	0.2970
	0.3070	0.3120		0.3100	0.2970		0.3130	0.2840
E10	0.2850	0.2790	E20	0.2910	0.2680	E30	0.2960	0.2590
	0.2791	0.2898		0.2850	0.2790		0.2910	0.2680
	0.2919	0.3073		0.2960	0.2955		0.3005	0.2825
	0.2960	0.2955		0.3005	0.2825		0.3045	0.2715
D10	0.2790	0.2700	D20	0.2855	0.2600	D30	0.2910	0.2515
	0.2722	0.2805		0.2790	0.2700		0.2855	0.2600
	0.2791	0.2898		0.2850	0.2790		0.2910	0.2680
	0.2850	0.2790		0.2910	0.2680		0.2960	0.2590
C10	0.2730	0.2610	C20	0.2800	0.2520	C30	0.2860	0.2440
	0.2653	0.2709		0.2730	0.2610		0.2800	0.2520
	0.2722	0.2805		0.2790	0.2700		0.2855	0.2600
	0.2790	0.2700		0.2855	0.2600		0.2910	0.2515
B10	0.2655	0.2500	B20	0.2730	0.2420	B30	0.2795	0.2355
	0.2568	0.2593		0.2655	0.2500		0.2730	0.2420
	0.2653	0.2709		0.2730	0.2610		0.2800	0.2520
	0.2730	0.2610		0.2800	0.2520		0.2860	0.2440
A10	0.2580	0.2390	A20	0.2660	0.2320	A30	0.2730	0.2270
	0.2482	0.2476		0.2580	0.2390		0.2660	0.2320
	0.2568	0.2593		0.2655	0.2500		0.2730	0.2420
	0.2655	0.2500		0.2730	0.2420		0.2795	0.2355

Notes:

1. Tolerance of Chromaticity Coordinates x,y : ± 0.005 .

Forward Voltage Bins

Bin code	Min Forward Voltage [V]	Max Forward Voltage [V]
1012	1.00	1.25
1215	1.25	1.50
1517	1.50	1.75
1720	1.75	2.00
2022	2.00	2.25
2225	2.25	2.50
2527	2.50	2.75
2730	2.75	3.00
3032	3.00	3.25
3235	3.25	3.50
3537	3.50	3.75
3740	3.75	4.00
4042	4.00	4.25
4245	4.25	4.50
4547	4.50	4.75
4750	4.75	5.00
5052	5.00	5.25
5255	5.25	5.50
5557	5.50	5.75
5760	5.75	6.00
6062	6.00	6.25
6265	6.25	6.50
6567	6.50	6.75
6770	6.75	7.00

Notes:

1. Forward voltage measurement tolerance: $\pm 0.05V$.
2. Forward voltage bins are defined at $I_F = 30mA$ operation.
3. Highlighted Black Box is possible output bins.

5. Part Number

2214-C70301H-AM

Part number is designated with below details.

2214 = Product family name.

C = Color [1]

7 = CRI (0=N/A; >70%=7; >80%=8; >90%=9)

030 = Test current [mA]

1H = Internal Code

AM = Automotive application

Note

[1] Color :

Symbol	Description
B	Cool White
C	Cool White
N	Neutral White
W	Warm White
PA	Phosphor Converted Amber
PR	Phosphor Converted Red
UB	Blue
IB	Ice Blue
SB	Sky Blue
UP	Purple
UG	Green
UY	Yellow
UYG	Brilliant Yellow Green
UPG	Pale Green
UA	Amber
UR	Red
SR	Super Red
RGB	RGB-Color
PYG	Phosphor Converted Yellow Green

6. Ordering Information

2214-C70301H-**ABCDEFGHJKLMNO-PQ-AM**

Part Number of the 2214	Order Code
2214-C70301H-AM	2214-C70301H-ABCDEFGHJKLMNO-PQ-AM

Order code contains information with below details :

ABCDEF = min/max wavelength or CCT






GHJK = min./max. luminous flux in [lm] or luminous intensity in [mcd]

LMNO = min./max. forward voltage

PQ = internal code

AM = Automotive Application


7. Mechanical Dimension



Notes:


- 1. Dimensions are in millimeters.
- 2. Tolerances unless mentioned are $\pm 0.1\text{mm}$.

8. Recommended Soldering Pad



9. Reflow Soldering Profile

Soldering Condition (Reference: IPC/JEDEC J-STD-020D)



Profile Feature	Pb-Free Assembly	Unit
	Recommendation	
Ramp-up rate to preheat 25 °C to 150 °C	3	°C /sec
Time of soaking zone 150 °C to 200 °C	120	sec
Ramp-up rate to peak	3	°C /sec
Liquidus temperature	217	°C
Time above liquidus temperature	100	sec
Peak temperature (max.)	260	°C
Time within 5°C of the specified peak temperature	30	sec
Ramp-down Rate (max.)	6	°C /sec

10. Packaging Information

● Product Labeling


RoHS Pb **EVERLIGHT** 5

CPN: XXXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXX-XXXXXXXX-XXXXXXXX-XXXXXXXX-XXXXXX
 P/N: XXXXXXXXXXXX
 XXXXXXXXXXX-XXXXXXXX-XXXXXXXX-XXXXXXXX-XXXXXX
 LOT NO: Y150716XXX-XXXXXXXX-XXXXXXXXXX
 QTY: 0123456789 HUE: XXXXXXXXXXXX
 CAT: XXXXXXXXXXXX REF: XXXXXXXXXXXX
 REFERENCE: BTPYYMDDXXXXX
 MSL-X MADE IN XXXXXX



- CPN : Customer's Product Number
- P/N : Everlight Part Number
- QTY : Packing Quantity
- CAT : Luminous Flux (Brightness) Bin
- HUE : Color Bin
- REF : Forward Voltage Bin
- LOT No : Lot Number


● Packing: Loaded Quantity 2000 pcs Per Reel



Notes:

1. Dimensions are in millimeters.


● Reel Dimensions



Notes:

1. Dimensions are in millimeters.
2. Tolerances unless mentioned are ± 0.2 mm.

● Moisture Resistant Packing Process




Notes:

1. Dimensions are in millimeters.
2. Tolerances unless mentioned are ± 0.2 mm.

11. Precaution for Use

1. Over-current-proof
Customer must apply resistors for protection; otherwise slight voltage shift will cause big current change (burn out will happen).
2. Assemblies
Do not stack assemblies containing LEDs to prevent damage to the optical surface of LEDs. Forces applied to the optical surface may result in the surface being damaged.
3. Soldering Condition
 - 3.1 When soldering, do not put stress on the LEDs during heating.
 - 3.2 After soldering, do not warp the circuit board.
4. Soldering Iron
Each terminal is to go to the tip of soldering iron temperature less than 350°C for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.
5. Repairing
Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



12. Sulfur Test Criteria

Products	Failure Criteria
Exterior Lighting products	Luminous Flux +/-20%, forward voltage +/-10%, color coordinates x,y +/-0.01, color wavelength +/- 2 nm Visual defect issue following Everlight's inspection criteria
Interior lighting products	Luminous Flux +/-30% or +/-50% for some application, forward voltage +/-10%, color coordinates x,y +/-0.02, color wavelength +/- 2 nm Visual defect issue following Everlight's inspection criteria

H2S test	Grade A0	Grade A1	Grade B0	Grade B1
Class A	Pass ΔIV , $\Delta Color$, ΔVF criteria No Corrosion	Pass ΔIV , $\Delta Color$, ΔVF criteria Corrosion without the impact on reliability and lifetime		
Class B			Pass ΔIV , $\Delta Color$, ΔVF criteria No Corrosion	Pass ΔIV , $\Delta Color$, ΔVF criteria Corrosion without the impact on reliability and lifetime

Condition for H2S and FMG	Description	
	H2S	FMG
Class A	15 ppm with duration 336 h at 40 °C and 90% RH	Duration 500 h at 25 °C and 75% RH. H2S concentration: 10ppb SO2 concentration: 200ppb NO2 concentration: 200ppb Cl2 concentration: 10ppb
Class B	10 ppm with duration 500 h at 25 °C and 75% RH	

Grade for H2S Test	Description
0	No Corrosion
1	Corrosion without the impact on reliability and lifetime